

Pure Green TOP LED (1210)

Lead(Pb) Free Product-RoHS Compliant

■ Applications

1. Lightings
2. Modules
3. Signal and Symbol Luminaires
4. Backlighting
5. Toys

■ Package Dimensions



Notes:

All dimensions in mm tolerance is $\pm 0.1 \text{ mm}$ unless otherwise noted.

■ Absolute Maximum Ratings (Ta = 25℃)

Items	Symbol	Absolute maximum Rating	Unit
Power Dissipation	P _D	100	mW
Forward Current(DC)	I _F	25	mA
Peak Forward Current*	I _{FP}	100	mA
Operation Temperature	T _{opr}	-30~ +85	℃
Storage Temperature	T _{stg}	-40 ~ +100	℃

*Pulse width $\leq 0.1\text{msec}$ duty $\leq 1/10$

■ Typical Electrical & Optical Characteristics (IF=20mA and Ta = 25℃)

Part No	Dominant Wavelength (nm)		Forward Voltage (v)		Luminous Intensity (mcd)		Reverse Current (μA)	50% Power Angle
	Min.	Typ.	Min.	Typ.	Min.	Typ.	Max.	Typ.
3528GCX2	515	520	2.8	3.2	563	780	50	120







■ Ranks Combination (IF = 20mA)

Rank	R1	R2	S1
Luminous Intensity(mcd)	563-703	703-878	878-1098


■ Notes

1. Tolerance of measurement of luminous intensity : $\pm 15\%$
2. Tolerance of measurement of dominant wavelength : $\pm 1\text{nm}$
3. Tolerance of measurement of forward voltage : $\pm 0.1\text{V}$


■ Typical Electrical/ Optical Characteristics Curves (Ta=25°C Unless Otherwise Noted)




■ Soldering heat reliability:
Lead Solder




Lead Free Solder



■ Packing Specifications:



■ Reel Specifications



Dimensions are specified as follows:mm

Notes:

Normal packing quantity: 2,000pcs/reel